

**ORIGINAL**



**InnoLIFT®**

Selfloader for Vans and Light Trucks



**FRENDIX®**

From Finland for the world

# THE FINNISH INNOVATION

## climbs inside the vehicle with the cargo

### Many More Deliveries Per Day

InnoLIFT helps support the use of faster and smaller delivery vehicles; decreased delivery waiting times; more efficient delivery routes in urban areas, suburbs and rural locations, and a more expansive potential workforce of delivery drivers.

### Completely Independent

InnoLIFT eliminates the need for lifts gates or other vehicle-mounted lifting equipment.

The driver can alone handle all deliveries up to 1000 kg (2,200 lbs), eliminating the need for a delivery assistant.

InnoLIFT can be easily moved from one delivery vehicle to another.

### Made in Finland

From welding to final assembly, the machines are handmade in Finland with over 20 years of experience to ensure reliable products for global market.

InnoLIFT models are available for various vans, trucks and trailers. Some models also offer solutions for special cases such as extra small transporters or closed pallets.

### InnoLIFT Customized Solutions

Because of our extensive global Frenndix sales network we're able to offer worldwide service for our international customers and a comprehensive understanding of local needs.



Closed pallet / USA



Small model / Japan



Drive motor/ Germany



Check out a video!

### InnoLIFT in Use



1. Load the cargo into the van.



2. Pull the support legs out and lift the chassis up.



3. Push the support legs back in.



4. Push the InnoLIFT and the cargo into the van.

## Technical details: Standard Models

Three standard models with the fastest delivery time: IM600.800, IL600.1000 and IXL500.1250. The IXXL has the highest lifting height and the IS is small in size.



**IM600.800**

Capacity: 600 kg  
Lifting height: 800 mm  
Loading height: 700 mm  
Overall lowered height: 1200 mm  
Chassis width: 790 mm  
Battery capacity: 12 V / 50 Ah



**IL600.1000**

Capacity: 600 kg  
Lifting height: 1000 mm  
Loading height: 900 mm  
Overall lowered height: 1400 mm  
Chassis width: 790 mm  
Battery capacity: 12 V / 50 Ah



**IXL500.1250**

Capacity: 500 kg  
Lifting height: 1250 mm  
Loading height: 1150 mm  
Overall lowered height: 1650 mm  
Chassis width: 790 mm  
Battery capacity: 12 V / 50 Ah



**IXXL400.1400**

Capacity: 400 kg  
Lifting height: 1400 mm  
Loading height: 1300 mm  
Overall lowered height: 1800 mm  
Chassis width: 790 mm  
Battery capacity: 12 V / 50 Ah



**IS600.700**

Capacity: 600 kg  
Lifting height: 700 mm  
Loading height: 600 mm  
Overall lowered height: 1100 mm  
Chassis width: 790 mm  
Battery capacity: 12 V / 50 Ah



## Technical details: Rough Terrain Models

ERT is a rough terrain model with a powerful drive motor. It is designed for more challenging surfaces such as uneven asphalt and low thresholds. Drive the InnoLIFT in and out with a remote control.



**ERT1000.1250**

Capacity: 1000 kg  
Lifting height: 1250 mm  
Loading height: 1050 mm  
Overall lowered height: 1745 mm  
Chassis width: 1350 mm  
Battery capacity: 24 V / 36 Ah



**ERT1000.1500**

Capacity: 1000 kg  
Lifting height: 1500 mm  
Loading height: 1300 mm  
Overall lowered height: 1995 mm  
Chassis width: 1350 mm  
Battery capacity: 24 V / 36 Ah



## Technical details: Self-Propelled Models

EL and EXL are self-propelled models with a drive motor.



**EL1000.1000**

Capacity: 1000 kg  
Lifting height: 1000 mm  
Loading height: 900 mm  
Overall lowered height: 1470 mm  
Chassis width: 1000 mm  
Battery capacity: 24 V / 36 Ah



**EXL1000.1250**

Capacity: 1000 kg  
Lifting height: 1250 mm  
Loading height: 1150 mm  
Overall lowered height: 1720 mm  
Chassis width: 1000 mm  
Battery capacity: 24 V / 36 Ah

## Technical details: 1000 kg Models

Both IL and IXL models can lift up to 1000 kg.



**IL1000.1000**

Capacity: 1000 kg  
Lifting height: 1000 mm  
Loading height: 900 mm  
Overall lowered height: 1450 mm  
Chassis width: 1000 mm  
Battery capacity: 12 V / 46 Ah



**IL1000.1250**

Capacity: 1000 kg  
Lifting height: 1250 mm  
Loading height: 1150 mm  
Overall lowered height: 1710 mm  
Chassis width: 1000 mm  
Battery capacity: 12 V / 46 Ah



## Technical details: Straddle Model and Manual Model

The US straddle model is designed for closed pallets. The IV model is manually operated.



**IXXL500.1400.US**

Capacity: 1000 kg  
Lifting height: 1500 mm  
Loading height: 1300 mm  
Overall lowered height: 1995 mm  
Chassis width: 1350 mm  
Battery capacity: 24 V / 36 Ah



**IV300.800**

Capacity: 300 kg  
Lifting height: 800 mm  
Loading height: 700 mm  
Overall lowered height: 1080 mm  
Chassis width: 710 mm  
Battery capacity: -

# FRENDIX®

From Finland for the world



## Frendix Oy

Vierikatu 11  
Järvenpää, Finland

[www.frendix.com](http://www.frendix.com)

[sales@frendix.fi](mailto:sales@frendix.fi)

Tel. +358 10 821 0700